

DATA SHEET

AMP-D225H

2-CHANNEL, 25W AMPLIFIER



The AMP-D225H is a two-channel class D amplifier delivering 25 watts per channel in a sleek, compact design. Because there is no need for internal cooling fans, the AMP-D225H can be placed in a conference room with virtually no audible noise. The ability to bridge channels gives even more power and flexibility to the AMP-D225H. The AMP-D225H is also equipped with four stereo inputs, four GPIO, and two RS-232 interfaces. It integrates easily with a variety of control systems and the USB input enables direct audio connection and volume control from a computer. It's audio performance, ease-of-use, and versatile feature set makes the AMP-D225H ideal for a variety of professional audio applications.

FEATURES

- Two channels; 25W per channel
- Bridgeable channels
- Class D amplifier topology
- Supports 4Ω and 8Ω outputs
- 4 GPIO for control of relays, switches, and sensors
- 3 band equalizer for bass, mid and treble control
- Auto standby mode
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' five-year warranty


ARCHITECTS & ENGINEERS SPECIFICATIONS

The amplifier shall provide 4 unbalanced input connections for receiving line level analog audio signals via RCA connectors. The amplifier shall provide two output channels rated for 25W each of maximum power into an 8-ohm load via Euroblock connector. The amplifier shall include 2 RS-232 connections for control data transmission into or out of the amplifier and such operation shall be externally programmable. The amplifier shall include 4 GPIO connections for the control of relays, switches, and sensors and such operation shall be externally programmable. The amplifier shall be CE marked, UL listed, and shall be compliant with the RoHS directive. Warranty shall be five years. The amplifier shall be Biamp® AMP-D225H.

AMP-D225H SPECIFICATIONS

Network Connection:	RJ-45 with Ethernet (CAT5e or better)	RS-232 / IR	
INPUTS		Number of Ports:	2 (bidirectional)
Number of Inputs:	4 (stereo)	Connector:	3-pin, 0.3-inch Euroblock
Connector:	RCA	Baud Rate:	1200 - 115200 bit/sec
Input Impedance:	< 100k Ω	Data Bits:	7, 8
Max Input Level:	2 Vrms	Parity:	Even, Odd, None
Input Gain (adjustable):	\pm 12 dB	Stop Bits:	1, 2
Wake on Signal:	Adjustable level	IR Frequency Range:	400 Hz to 500 kHz
OUTPUTS		Power:	24V DC 50W
Number of Channels:	2	Cooling:	Convection
Maximum Rated Output:		Overall Dimensions	
Single Channel, 4Ω:	35W	Height:	1.5 inches (37 mm)
Single Channel, 8Ω:	25W	Width:	8.6 inches (218 mm)
Bridged, 4Ω:	55W	Depth:	2.8 inches (70 mm)
Bridged, 8Ω:	35W	Weight:	1.1 lbs (0.5 kg)
Minimum Operational Load:	2 Ω	Environmental	
THD+N (20 Hz - 20 kHz, @ 1W):	< 0.1 %	Ambient Operating Temperature Range:	32 - 86° F (0 - 30° C)
Connector:	4-pin, 0.3-inch Euroblock	Humidity:	10-90% relative humidity (non-condensing)
USB		Altitude:	0-6,600 ft (0-2000m) MSL
Connector:	USB 2.0 Type-B	Compliance:	
Bit Depth:	16-bit		FCC Part 15B (USA)
Sample Rate:	48kHz		UL listed (USA and Canada)
GPIO			CE Marked (Europe)
Number of Ports:	4		RoHS Directive (Europe)
Connector:	5-pin, 0.3-inch Euroblock		
Type:	Open drain		
Input Trigger Low:	< 1V DC		
Input Trigger High:	> 4V DC		
Isolated Output:	No		
Max Voltage:	24V DC		
Max Current:	0.5 A		

AMP-D225H REAR PANEL



Biamp is either a trademark or registered trademark of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.



A: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA

T: +1 503.641.7287

W: www.biamp.com

BIADS-1048-2109-EN-RI