

eLumen8

CABLE DATASHEET


SPECIFICATION

Description: INSTALL LSZH 2 Core 2 x 2.5mm² Speaker Cable SP2X2.5B

Type: Speaker cable

Versions: CABL626 - White, 100m length
CABL626B - White, 500m length
Also available by the metre

CONSTRUCTION



2 core 0.75mm² loudspeaker cable for general purpose 100V loudspeaker applications in fixed installations. The cable is constructed from two multi-strand, oxygen-free copper cores within a narrow diameter thermoplastic outer jacket. The loudspeaker cable is Low Smoke Zero Halogen to comply with fixed installation requirements.

Conductor: Material - Bare Copper (OFC)
Construction - 50 x 0.254mm
Cross section - 2.5mm² x 2

Insulation: Material - Low Smoke, Halogen-Free Thermoplastic Compounds (LSHF)
Thickness - 0.38mm
Diameter - 2.9mm x 2 core
Colour - 1) Black, 2) Red

Ripcord: Material - Nylon

Outer jacket: Material - Low Smoke, Halogen-Free Thermoplastic Compounds (LSHF)
Thickness - 0.6mm
Diameter - 7.0mm

OPERATION TEMP.

-15°C ~ 60°C

ELECTRICAL CHARACTERISTIC

Conductor resistance: 7.2Ω/km