

# Freedom Par T6

- 100% TRUE wireless, battery-operated, tri-color (RGB) LED uplight with built-in D-Fi transceiver
- New secondary optics provide perfect color blending with nearly no artifacts
- Magnetic diffuser pops on or off with ease and widens the coverage area
- Adjustable run times ensure the fixture will last the length of the event
- OLED display allows for full-text and to easily change fixture's settings
- Built-in RF receiver for wireless control using the RFC or RFC-XL optional remotes
- Adjust the projection angle using the spring-loaded kickstand
- Built-in glare shield protects light spillage and eye fatigue
- Extend the fixture's lifespan with the onboard charge and discharge protection circuitry
- Achieve smooth LED fading with built-in dimming curves
- Ultra-Compact and lightweight design easily fits inside sticks of TRUSST®

## Specifications

- DMX Channels: 3, 5 or 13
- Light Source: 6 LEDs (RGB) 3 W, (0.7 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 27 Hz
- Beam Angle: 13°
- Field Angle: 29°
- Operating Frequency: 2.412 to 2.484 GHz
- Illuminance : 1876 lux @ 2 m
- Lumens : 775
- Run Time (adjustable): 3, 5, 8, or 12 hrs
- Recharge Time : 4 hours
- Max Unobstructed Distance: 600 ft (183 m)
- Input Voltage: 24 VDC, 3.5A A (external power supply: 100-230 VAC, 50/60 Hz)
- Power and Current: 35 W, 0.52 A @ 120 V, 60 Hz
- Power and Current: 35 W, 0.33 A @ 230 V, 50 Hz
- Bracket Mounting Hole: M12
- Weight: 2.6 lb. (1.2 kg)
- Size: 3.9 x 3.9 x 5.1 in (98 x 98 x 130 mm)
- Optional Controllers: RFC, RFC-XL, FlareCon Air
- Approvals: CE , UKCA , ROHS , FCC

