

SlimPAR Q6 ILS

- ILS compatibility for use in the ILS ecosystem
- Low-profile, high-output quad-color (RGBA) LED Par
- D-Fi™ USB compatibility for wireless Master/Slave or DMX control
- Generate a broad spectrum of colors and achieve natural-looking color temperatures with punchy amber LEDs
- Convenient access to RGBA color mixing and static colors with or without DMX
- Flicker-free operation suitable for on-camera use
- Increase standalone versatility with multiple user-configurable settings
- Save time running cables and extension cords by power linking multiple units
- Easily control static colors and automated programs with the optional IRC-6 remote
- Fits best in the CHS-30 VIP gear bag
- Compact design easily fits inside sticks of TRUSST®

Specifications

- DMX Channels: 4 or 9
- DMX Connectors: 3-pin XLR
- Light Source: 6 LEDs (quad-color RGBA) 4 W, (1.5 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Beam Angle: 17°
- Field Angle: 29°
- Illuminance: 2,016 lux @ 2 m
- Power Linking: 21 units @ 120 V; 37 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 26 W, 0.4 A @ 120 V, 60 Hz
- Power and Current: 27 W, 0.2 A @ 230 V, 50 Hz
- Weight: 2.8 lb (1.3 kg)
- Size: 8.8 x 2.5 x 7.5 in (224.5 x 64 x 191.5 mm)
- Optional Controllers: IRC-6, D-Fi USB
- Approvals: CE, RoHS, UKCA

