

Product type      Audio connector) \_\_\_\_\_  
Product NO.      SL4FX-N \_\_\_\_\_  
Customer          \_\_\_\_\_

	(APPROVAL)	(AUDIT)	(COMPILE)
Manufacturer			

	(APPROVAL)	(AUDIT)	(ACCEPT)
(Customer)			

## (Product Appearance)



## (Product features)

- ✓ (Quick, simple locking system)
- ✓ (Connect reliably)
- ✓ (Small size of product)

## (Technical parameters)

### (Electrical parameters)

(Contacts NO.)	4
(Rated current)	40A rms
(Rated voltage)	250V
(Contact resistance)	$\leq 5\text{m}\Omega$
(Dielectric strength)	500V DC
(Insulation resistance)	$> 1000\text{M}\Omega$

### 2. (Mechanical parameters)

(Service life)	$> 1000$
(Wire diameter)	$4\text{mm}^2$ / O. D: $7\sim 14.5\text{mm}$

### 3. ( Material and environmental parameters )

( Shell )	PA66+30%GF
( Contacts )	Cu alloy
( Contact surface )	Ag
( Flame-retardant grade )	UL94-V0
( Temperature range )	-30° to +80°

### 4. ( Standard )

( Standard )	IEC61984
--------------	----------

### (Product Profile)

