



## NLT4FX

4 pole female cable connector, nickel housing, chuck type strain relief

The speakON STX Series was especially designed for heavy duty amplifier-loudspeaker applications like professional touring. The extremely rugged and durable STX Series features an all metal housing.

### Features & Benefits

- Current rating 40 A continuous, 50 A audio signal with 50% duty cycle
- Sealing ring provides weatherproof IP54 rating in mated condition
- Extra large solder contacts for up to 6 mm<sup>2</sup> (AWG 10) wires
- Robust and durable all metal housing
- Reinforced metal quick lock system for ease and precise locking
- Mate with all available speakON products

**Technical Information**

Product	
<b>Title</b>	NLT4FX
<b>Connection Type</b>	speakON
<b>Gender</b>	female

Electrical	
<b>Contact resistance</b>	< 2 m $\Omega$ (after lifetime)
<b>Dielectric strength</b>	4 kVdc (peak)
<b>Insulation resistance</b>	> 10 G $\Omega$
<b>Rated current per contact</b>	40 A rms continuous
<b>Rated current per contact</b>	50 A audiosignal, duty cycle 50 %
<b>Rated voltage</b>	250 V ac
<b>Attention</b>	speakON is NOT to be used as an AC mains or power supply connector!

Mechanical	
<b>Cable O.D.</b>	9 - 16 mm
<b>Cable retention</b>	$\geq$ 220 N (subject to cable O.D. and material)
<b>Lifetime</b>	> 5000 mating cycles
<b>Wiresize</b>	6 mm <sup>2</sup>
<b>Wiresize</b>	10 AWG
<b>Wiring</b>	Solder contacts
<b>Locking device</b>	Quick Lock (latch)

Material	
<b>Contact plating</b>	4 $\mu$ m Ag
<b>Contacts</b>	Brass (CuZn39Pb3)
<b>Insert</b>	Polyamide (PA 6 30 % GR)
<b>Locking element</b>	Zinc diecast (ZnAl4Cu1)
<b>Shell</b>	Zinc diecast (ZnAl4Cu1)
<b>Strain relief</b>	Polyacetal (POM)

**Environmental**

<b>Flammability</b>	UL 94 HB
<b>Protection class</b>	IP 54 (mated condition)
<b>Solderability</b>	Complies with IEC 68-2-20
<b>Temperature range</b>	-30 °C to +80 °C