



## CH-2

Order No.: 0257240

### PRODUCTINFOS

#### **The wideband multifrequency system UF-20... from JTS**

is the perfect solution for stage applications of high requirements due to an excellent flexibility and reliability.

The device impresses with a convenient setup function, REMOSET technology, 75 MHz bandwidth, 3,000 frequencies which can be selected as desired and additional professional features, e.g. active carrier analysis method.

#### **Charging station,**

for transmitters UF-20TB/5, JSS-20/5, JSS-4B/5, R-4TBM/5 and RU-G3TB/5.

- For simultaneously charging rech. batteries of 2 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 3 hours
- Each slot with LED for indicating a fault and battery charging status
- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge
- Power is provided via enclosed power supply
- Dimensions: 165 x 72 x 99 mm

## TECHNICAL SPECIFICATIONS

### CH-2

Description	charging station
Colour	black
Suitable for	transmitters UF-20TB/5, JSS-20/5, JSS-4B/5, R-4TBM/5, RU-G3TB/5
Power supply	via enclosed power supply
Dimensions	165 x 72 x 99 mm
Weight	315 g
Packing unit	1
Packing dimensions (W x H x L)	0.115 x 0.095 x 0.245 m
Gross weight	0.865 kg
Net weight	0.513 kg