



CM-601

Order No.: 0235010

PRODUCTINFOS

Electret boundary microphone

- For theatrical performances, discussions, conferences and in churches
- A direct alignment to the sound source is not essential due to the special characteristics of a boundary microphone
- Dual low cut filter (80 Hz/120 Hz)
- Configurable push-button (PTT, PTM or switching function)
- Standby LED
- Robust and shock-absorbing body
- Elastic cartridge suspension for preventing structure-borne noise and impact sound

TECHNICAL SPECIFICATIONS

CM-601

Description	boundary microphone
Transmission method	cable
Polar pattern	semi-cardioid

CM-601

System	electret
Audio frequency range	30-12,000 Hz
Nominal impedance	100 Ω
Sensitivity	2.2 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 15-48 V, phantom power
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Dimensions	72.5 x 22 x 110 mm
Weight	0.269 kg
Connection	XLR, bal.
Packing dimensions (W x H x L)	0.155 x 0.06 x 0.16 m
Gross weight	0.399 kg
Net weight	0.269 kg

CM-601

Width	72.5 mm
Height	22 mm
Depth	110 mm
Weight	0.269 kg