



## FGM-170

Order No.: 0236070

### PRODUCTINFOS

#### **Floor stand microphones,**

with carbon fibre boom.

- 3 high-quality back electret microphone cartridges with different polar patterns
- Low cut switch (80 Hz)
- 10 dB attenuation, switchable
- Extra lightweight (105 g) but very robust carbon fibre boom (1.46 m) with miniature gooseneck
- Structure-borne noise isolated diecast base plate
- Supplied with 2 replacement cartridges, connection cable and windshield
- Delivery consists of 2 boxes

**FGM-170: with long shaft, for overhead miking**

**FGM-62: with short shaft, for front miking**

#### **Floor stand microphone,**

with carbon fibre boom.

- 3 high-quality back electret microphone cartridges with different polar patterns
- Low cut switch (80 Hz)
- 10 dB attenuation, switchable
- Extra lightweight (105 g) but very robust carbon fibre boom (1.46 m) with miniature gooseneck
- Long shaft, for overhead miking
- Structure-borne noise isolated diecast base plate
- Supplied with 2 replacement cartridges, connection cable and windshield
- Delivery consists of 2 boxes

## TECHNICAL SPECIFICATIONS

### FGM-170

Description	microphone floor stand
Transmission method	cable
Polar pattern	cardioid, supercardioid, omnidir.
System	back electret
Audio frequency range	50-18,000 Hz
Nominal impedance	220 Ω
Sensitivity	16 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 12-48 V, phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	1.46 m (boom) 1.6 m (stand)
Weight	3.6 kg
Connection	cable with 3-pole mini XLR to XLR
Packing dimensions (W x H x L)	0.3 x 0.26 x 1.51 m
Gross weight	4.3 kg
Net weight	3.72 kg