



GML-5218

Order No.: 0234570

PRODUCTINFOS

Electret gooseneck microphones with LED

- 3 replaceable microphone cartridges with different polar patterns (cardioid, supercardioid and omnidirectional)
- Excellent speech intelligibility
- -10 dB PAD switch
- Switchable low cut filter
- LED for indicating operating status
- Solid and high-quality workmanship to ensure a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power or microphone base DMS-5

TECHNICAL SPECIFICATIONS

GML-5218

| | |
|---------------------|----------------------|
| Description | gooseneck microphone |
| Version | LED |
| Transmission method | cable |

GML-5218

| | |
|--------------------------------|---------------------------------|
| Polar pattern | cardioid/supercardioid/omnidir. |
| System | back electret |
| Audio frequency range | 80-18,000 Hz |
| Nominal impedance | 220 Ω \pm 30% |
| Sensitivity | 16 mV/Pa |
| Max. sound pressure | 125 dB |
| Power supply | DC 48 V phantom power |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 615 mm |
| Weight | 245 g |
| Connection | XLR, bal. |
| Packing dimensions (W x H x L) | 0.09 x 0.06 x 0.655 m |
| Gross weight | 0.465 kg |
| Net weight | 0.245 kg |