



JSS-20/5

Order No.: 0257200

PRODUCTINFOS

The wideband multifrequency system UF-20... from JTS

is the perfect solution for stage applications of high requirements due to an excellent flexibility and reliability.

The device impresses with a convenient setup function, REMOSET technology, 75 MHz bandwidth, 3,000 frequencies which can be selected as desired and additional professional features, e.g. active carrier analysis method.

Dynamic hand-held UHF PLL transmitter

- Dynamic microphone cartridge (cardioid polar pattern) with minimised feedback susceptibility as well as suppression of handling noise/structure-borne noise
- Bandwidth: 75 MHz
- 15 groups, each with up to 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (-15 dB to +15 dB)
- Lock function/mute function
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

- Supplied with robust transport case, stand clamp and 8 ID caps

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

tools4music 06/2015

“With the wireless system UF-20, JTS is able to offer an absolutely professional system. Despite numerous features, the menu navigation can easily be followed and understood. The REMOSET function allows you to simultaneously adjust up to 48 transmitters and receivers. In addition, important functions of the hand-held transmitter can remotely be controlled via the receiver which is particularly helpful at festivals. It allows you to quickly adjust the microphone sensitivity. The system also impresses with an appealing design and a neat workmanship.”

TECHNICAL SPECIFICATIONS

JSS-20/5

Description	hand-held microphone
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	530-605 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	> 20 h
Audio frequency range	50-18,000 Hz
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 50 mm x 260 mm
Weight	340 g
Packing dimensions (W x H x L)	0.175 x 0.085 x 0.365 m
Gross weight	1.075 kg
Net weight	0.855 kg