



ST-6060 UNIVERSAL GOOSENECK MICROPHONE BASE

Thank you for choosing JTS ST-6060 Universal Gooseneck Microphone Base. In order to obtain the best efficiency, you are recommended to read this manual before using.

Feature

The ST-6060 is a full featured microphone base. Rugged metal body isolates vibration and touch noise effectively. Membrane switch virtually eliminates switch noise. Three talking modes, Push-To-Talk, Push-To-Mute and Push-On/Push-Off are provided. Low cut circuit makes installation easier. Prospective design keeps space for expansion.

Parts Identification

- ① Stand Base
- ② On / Off Switch
- ③ Power On/Off LED Indicator
- ④ Input Socket (3P XLR, Female)
- ⑤ Cable With 3-pin Male XLR
- ⑥ Low Cut Switch
- ⑦ Switching Mode Selector
- ⑧ Rubber Pad



Use Instruction

Installation

- (1) Plug the microphone onto the input socket. (Figure 1)
- (2) Connect the cable to a mixer or amplifier. (Figure 1)

Note: Use a gooseneck microphone that has no LED indicator is recommended.




Figure 1

Switching Mode Selecting

There are four operating modes, which can be selected on the bottom of the stand base.

Use DIP switches 1 and 2 to configure the mute button, as follows.

SW1	SW2	
<input type="checkbox"/>	<input type="checkbox"/>	Mom. OFF: push-to-mute
<input type="checkbox"/>	<input checked="" type="checkbox"/>	Mom. ON: push-to-talk
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Push ON/OFF: Mic is active when powered on
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	Push ON/OFF: Mic is mute when powered on

Note: SW3/SW4 No Function

LED Indicator

LED indicator shows the On/Off status . When the LED lights up, the microphone is ON to talk.

Specification

Frequency Response..... 20 ~ 20,000Hz

Power Requirement..... Phantom power 12-48V

Current Consumption -Stand-by <4mA

Switches..... Push control: on/off

Function selection: push ON/OFF, push-to-mute, push-to-talk,

Low cut switch:150Hz / -10dB(±2dB)

Cable length:4M

Connector..... Input:3-pin female XLR

Output:Cable with 3-pin male XLR

Net Weight..... 745 grams

Dimension (mm)

