

Ultra-compact double band pass, passive sub woofer with one 8" transducer with double independent coil and rubber suspension. 124 dB SPL (600W). **NEW UPGRADE.**



Key features

- Ultra-compact light weight
- Background sound reinforcement
- ARK processor optimised preset
- White & black colour optional
- Rugged design

Applications

- Club & bar installations
- Theatres
- Houses of worship
- Broadcast
- Restaurants
- Multi media spaces

General description & specifications

The SUB-08 is an ultra compact double band pass subwoofer delivering highperformance for background sound applications. It uses one 8" transducer with rubber surround and double independent coil.

The SUB-08 has been designed to be used with the QB-5 to extend the low frequency support.

Technical Data

Components	
• LF	1 x 8" transducer
Frequency range	43 Hz – 160 Hz (-10dB)
Frequency response	47 Hz – 154 Hz (± 3dB)
Sensitivity	93 dB (1W @ 1m)
Max SPL	118 dB – 124 dB peak
Coverage angle	360° single unit
Rated power	300 W AES
Program power	600 W AES
Nominal impedance	8 Ω
Connectors	2 x Neutrik Speakon NL4MP
Finish	Polyurea coating
Material	15 mm Premium birch plywood
Dimensions	268 x 641 x 304 mm (H x W x D)
Weight	10 Kg (22 lbs)

Dimensional Drawing

